High Pressure Equipment

Line Filters

The line filters as shown utilize sintered stainless steel filter discs 3 pc./set. Porosities are available as per the chart to the right. If not otherwise specified, 100 micron

filter discsare supplied. (One micron = 0.001 millimeters). Material of bodies and end covers is high tensile 316 stainless steel. Standard tubing glands and collars are provided unless otherwise specified.

- FLOW

	Pressure Rating			Hex	Micron Size Filter Available					
Catalog No.	psi	Connections	Length	Size	0.5	2	5	10	40	100
40F-51HF9	40,000	^୬ /₁ [#] HIGH PRESSURE	5 ³ /4"	1 ¹ / ₂ "						
60F-51HF2	60,000	¹ /8" HIGH PRESSURE	4 ¹¹ / ₁₆ "	1 ¹ / ₂ "	•		•			
60F-51HF4	60,000	¹ / ₄ " HIGH PRESSURE	4 ⁷ /8"	1 ¹ / ₂ "	٠					
60F-51HF6	60,000	³ /8" HIGH PRESSURE	5 ¹ / ₄ "	1 ¹ / ₂ "	•		٠		٠	
60F-51HF9	60,000	°/ " HIGH PRESSURE	5 ³ /4"	1 ¹ / ₂ "						